INFORMATION SHEET #2

EYEWASH STATIONS

Consult the Industrial Establishment Regulations under the Ontario Occupational Health and Safety Act for detailed information and specific requirements and restrictions.

- 1. Eyewash stations must be provided where a worker is exposed to a potential hazard of injury to the eye due to contact with a biological or chemical substance.
- 2. Instruct all employees, professors, students, volunteers and visitors in the location and proper use of eye/face washes.
- 3. Eyewash stations must be checked for flow by the faculties weekly. The records of these inspections must be kept.
- Eyewash stations will receive full maintenance every 12 months (flow, spray, volume, valve, etc.).
 The records of these inspections must be kept.
- 5. Eyewash stations must be installed within 10 seconds of a hazard and with an unobstructed travel path.
- 6. Eyewash stations must be installed and used according to manufacturer's specifications.
- 7. Identify eyewash station locations with highly visible signs.
- 8. Eyewash stations must be easily accessible at all times.
- 9. Area around eyewash stations shall be well lit.
- 10. Eyewash stations will operate with water supplied from the main water supply for each building.
- 11. Spray jet patterns and flow rates will operate within ANSI specified guidelines.
- 12. Stay-open valves must be in place and be operable to allow an individual to use both hands to hold eyes open or remove clothing (if required).
- 13. Wastewater from stations should not create a hazard.
- 14. Drains should be provided where feasible and/or required.
- 15. When possible, construction and operation of eye/face wash stations must meet or exceed the requirements of ANSI Z358.1-2004.